



COMBO

**The combination
sewer cleaner that has
been setting industry
standards since 1986**

- Single or dual engine configuration
- Gas or diesel auxiliary engines available on dual engine machines
- Single axle
 - 5, and 10-yard debris tank options
- Tandem axle
 - 10, 12, and 15-yard debris tank options
- 3-stage centrifugal fan or PD blower
- Aeroboost Performance Package available on dual-engine configurations

WHY A VAC-CON COMBO

Select from a range of options to custom build your combo machine, fit to your application.

Simple, user-friendly operation.

Hydrostatically-driven vacuum and/or water.

60-in dump height while maintaining an overall height under 12-ft.

1/4-in. Corten steel debris tank with stainless steel micro filtration screen.

Cyclonic separation.

Standard flat rear door with hydraulic wedge-type locks.

Water tank locations provide the lowest center of gravity on the market.

3/8-in. cross-linked polyethylene water tank capacity up to 1,500-gallons.

Water systems up to 3,000 PSI and 100 GPM with smooth, continuous flow and pressure.

180-degree articulating hose reel with up to 800-ft. x 1-in. hose capacity and an outrigger leg for additional stability.

6-ft. or 10-ft. telescopic boom with 270-degree rotation.

Hydro-excavation, cold weather, and Aeroboost Performance packages available.

